

FIG. 1


240
TOP FSM
212
CBUS REGISTERS
210
CLOCKGEN
goCoeff
goFilter
CBUS to MCP
CFSM
214
242
OPERATION CONTROL & CONTEXT/DATA READ/WRITE REQUEST/CONTROL
DRWFSM
230
HFL_next_rd3
HFL_next_rd1
HFL_next_rd2
HFL_next_wr1
HFL_next_wr2
HFL_INpixel
HFL_INcontext
FUNCTIONAL UNIT DATAPATH
228
HFL_OUTpixel
HFL_OUTcontext
clk
HFL_INcoeff
COEFF MEMORY
224
COEFF. MEMORY WRITE LOGIC
222

FIG. 2


210
clkbranch
310
clk CTG1
blkEn_
HFL_top_hold
4x
clktbuf
top FSM
312
clk CTG2
blkEn_
HFL_cw_hold
3x
clkc0buf
coeff write
314
clk CTG3
blkEn_
HFL_cr_hold
8x
clkc1buf
8x
clkc2buf
8x
clkc3buf
coeff read
316
clk CTG4
blkEn_
8x
clkc4buf
coeff read
318
clk CTG5
blkEn_
HFL_f_hold
7x
clkd1buf
6x
clkd2buf
6x
clkd3buf
datapath control
clk CTG6
blkEn_
8x
clkd0buf
4x
clkd4buf
datapath control
320

FIG. 3



end_cond= (FILTER && LDCF) ? (Fdone1 && Cdone1)
: ((FILTER) ? Fdone1 : Cdone1



FIG. 4

222


Cdone
Cdone=0
CIDLE
goCoeff
crreq=1
crcounter=255
(crcounter==0)
Cdone=1
bcount=0
wphi=0
ldstate=0
520
CW1
540
CFILL
510
560
CW2
~crcounter
crcounter--
bcount++
(bcount==7)
=> wphi++
(crcounter==3)
=> crreq=0
ldstate=1
CW3
580

FIG. 5


HFL_incoeff[9:0]
Decoder & permutator
bend[7:0] (byte enables)
c_data_in[63:0]
bcount[2:0]
RD_HI
rphi[5]
1
0
topbit
PHASE32
MMIO register value
c_rd_addr={topbit,rphi[4:0]
c_wr_addr={WR_HI,wphi[4:0}

FIG. 6A


BANK2RD
ldstate
LD_COEFF
rd_en
wr_en
c_datain
datain
c_wr_addr
wr_addr
bend
byte_en
c_rd_addr
rd_addr
dataout
BANK1
BANK2
C123456[63:0]
BAN2RD
0
1
bit separator
C1[9:0] =C123456[9:0]
C6[9:0] =C123456[61:52

FIG. 6B


a: Polyphase direct
b: Polyphase transposed
c: FIR 12
d: FIR 11
e: Mirror at begin
f: Mirror at end
PIPE REG.
DATAPATH STRUCTURE
Couples with S* to decide mux control of registers
shiftlhi
shiftlo
EMS
SIU
SID
S2D
S2U
S3DAB
S3U
S3DC
CONTEXT IN
LINE IN
RNDCNST
RSVALcur
RND
PT
C1
C2
C3
C4
C5
C6
Slice 1
Slice 2a
Slice 2b
Slice 3a
Slice 3b
Slice 3c
16 MSBs
CR
ACCUMULATE (CSA + ripple carry add)
ZOOM[11:2]
sum
c12
HCcur
ZOOM[15.0]
RSVALcur
CCS
CONTEXT OUT
CLAMP
FILTER OUT
Slice 4

Fig. 7


810
820
HFL_INpixel
852
8206
x12
x6
direct input pipeline
820a
x6
multiplier stage
x?
x5
accumulation
HFL_next_wr
1
data
835
generate step, HFL_next_rd1
5/6 MSBs = phase
@
BANK2RD
856
N Byte Incr
834
1/z int Reg
carry
1/z frac Reg
837
BANK2WR
833
1/z Incr Integer
1/z Incr Fraction
836
832
manage 1/z factor (variable zoom)
data
824
@
858
HFL_INcoeff
812
generate address, HFL_next_rd3
831

FIG. 8



FIG. 9



Direct Input Pipeline

sent to the multiplier stage

FIG. 10



FIR12

FIG. 11



FIR11

FIG. 12



Polyphase

FIG.13


mirror
pixel
M
S*U
combination
mux
M=P=X=D=Q=13 bits wide
from
prev
FF
0
1
2
X
D
Q
to
next FF
TOP FF
IN SLICE
P
mult out
(upper 13 bits)
sel={shifthi,shiftlo}
Q[12:0]
{Q[12:10],X[9:0]}
{X[12:10],Q[9:0]}
X[12:0]
D

FIG. 14


BOTTOM FF
IN SLICE
to
next FF
Q
D
Y
top FF in
T
from
previous
FF
0
1
2
S*D
F
Q=D=F=T=13 bit wide
sel={shifthi,shiftlo}
D
Q[12:0]
{Q[12:10],Y[9:0]}
{Y[12:10],Q[9:0]}
Y[12:0]
mult out
(lower 13 bits)

FIG. 15